

HT105D

Socket Tester with RCD



Specifications	HT105D
Voltage range	AC 48~250V
RCD test	>30mA
Socket connection detection	Correct connection
	Open ground
	Open neutral
	Open live
	Live wire and ground wire reverse
	Live wire and neutral wire reverse
	Live wire and ground wire reverse, missing ground wire
Weight	Approx. 50g
Size	65mmx62mmx58mm
Safety rating	EN61010-1,-2-030; EN61326-1, CAT II 300V



Socket Tester with RCD

HT105E

Specifications	HT105E
Voltage range	AC 48~250V
RCD test	>30mA
Socket connection detection	Correct connection
	Open ground
	Open neutral
	Open live
	Live wire and ground wire reverse
	Live wire and neutral wire reverse
	Live wire and ground wire reverse, missing ground wire
Weight	Approx. 50g
Size	65mmx62mmx58mm
Safety rating	EN61010-1,-2-030; EN61326-1, CAT II 300V



HT106D

Socket Tester with Voltage Test & RCD



Specifications	HT106D
Voltage range	AC 48~250V
RCD test	>30mA
Voltage measurement (48V~250V/45~65Hz)	✓
LCD display	✓
Backlight	✓
Socket connection detection	Correct connection
	Open ground
	Open neutral
	Open live
	Live wire and ground wire reverse
	Live wire and neutral wire reverse
	Live wire and ground wire reverse, missing ground wire
Weight	Approx. 50g
Size	65mmx62mmx58mm
Safety rating	EN61010-1,-2-030; EN61326-1, CAT II 300V



Socket Tester with Voltage Test & RCD

HT106E

Specifications	HT106E
Voltage range	AC 48~250V
RCD test	>30mA
Voltage measurement (48V~250V/45~65Hz)	✓
LCD display	✓
Backlight	✓
Socket connection detection	Correct connection
	Open ground
	Open neutral
	Open live
	Live wire and ground wire reverse
	Live wire and neutral wire reverse
	Live wire and ground wire reverse, missing ground wire
Weight	Approx. 50g
Size	65mmx62mmx58mm
Safety rating	EN61010-1,-2-030; EN61326-1, CAT II 300V

